HellermannTyton



A modern and cost effective medium volume printer



Thermal Transfer Printer

TT430

The TT430 is perfect for printing on HellermannTyton materials such as self-adhesive labels, shrinkable tubing and identification tags. Thanks to its low weight and compact construction, the TT430 integrates seamlessly into any workstation. It is easy to use due to its intuitive touch display and clear status messages which can be shown in multiple languages. The optional cutter and perforator make this printer ideal for a wide range of applications. 300 dpi resolution ensures that barcodes, warning symbols, logos and text are as sharp as they can be.

Features and Benefits

- Medium volume single sided printing
- Print on THTT DS, TLFX DS, TDRT DS and TULT DS ("Ladder" products)
- Print on THTT, TLFX, TDRT, TULT, and TCGT (Continuous tubing)
- Print on TAGHT, TAGLF, TAGDR, TAGUL, Tiptags
- · Print on adhesive labels
- · Uses standard ribbons
- · Barcodes: standard and 2D
- Print speed up to 125 mm/s (30mm/s recommended for "Ladder" products and tubing)
- · Adjustable label sensor
- Multiple language selection
- Windows drivers: 32/64 bit for Windows XP, Windows Vista, Windows 7 and Windows 8
- Options: Cutter (556-00452) and External Reel Holder (556-00451)



TT430 thermal transfer printer.

Print Method	Thermal Transfer	
Print Head Type	300 dpi, flat type	
Print Speed	up to 125 mm/s	
Max. Print Width	106 mm	
Label Height Max (metric)	1,000 mm	
Printer Interfaces	USB 2.0, Ethernet 10/100 Base T	
Supported Barcodes, Printer	Standard and 2D	
Printer Memory	64 MB RAM	
Dimensions W x H x D	253 mm x 189 mm x 322 mm	
Weight	4 kg	





TYPE	Pack Cont.	Article-No.	
TT430	1 pc.	556-00450	

Subject to technical changes.

ТҮРЕ	Description	Pack Cont.	Article-No.
S430 Cutter	Cutter for TT430	1 pc.	556-00452
P430 Perforator	Perforator for TT430	1 pc.	556-00456
TT External Reel Holder	External Reel Holder	1 pc.	556-00451
TT430 300dpi Printhead	Printhead for TT430	1 pc.	556-00453
TT430 Print Roller	Print Roller for TT430	1 pc.	556-00454

Subject to technical changes.







