

Heat Shrink Tubing

ShrinkKit 321

ShrinkKit 321

Kits with optimised 3:1 shrink ratio

HellermannTyton

ShrinkKit 321 is the family of three heat shrink tubing assortments in attractive and handy assembly kits. The range consists of ShrinkKit 321 Universal, ShrinkKit 321 Basic and ShrinkKit 321-A (a dual wall tubing). With their ideal shrink ratio of 3:1 these products replace many differently sized tubing solutions by fitting almost any heat shrink requirements. Choosing the required product is simplicity itself as the tubings are clearly identified by size, length and content printed on every compartment of the assortment boxes.



The right tubing size at hand for any application: ShrinkKit 321 Universal, ShrinkKit 321-A and ShrinkKit 321 Basic.

ShrinkKit 321 Universal

Features and Benefits

The attractive and reusable kit is the solution for almost every heat shrink task. The big variety of sizes, colours and lengths offers a wide number of applications: insulation, bend protection or identification. The 3:1 shrink ratio can easily cope with substrates of varying diameter.

When all tubing has been consumed the case can be re-used for storing nails, screws, nuts, fish hooks, et cetera. The size of the compartments can be changed by simply moving the yellow space dividers.

Content

This kit contains a range of general purpose tubing lengths clearly sorted in various sizes and colours. Its ideal shrink ratio of 3:1 replaces many differently sized tubings. A diameter range from 1 mm to 20 mm can be covered with ShrinkKit 321 Universal.



Shrink ratio 3:1 for a wider range of applications.

Material Data

Material	Polyolefin, cross-linked (POX)
Shrink Ratio	3:1
Longitudinal change after shrinkage	+5%/-10% max.
Minimum Shrink Temperature	+90 °C
Operating Temperature	-55 °C to +135 °C
Insulation Class	B (VDE 0530)
Dielectric Strength	20 kV/mm according to ASTM D 2671
Flammability	self-extinguishing (except for transparent)

Technical Table

Article-No.	Comp.	Supplied Ø D min.	Recov. Ø d max.	Length (L)	Colour	Number of tubes
380-03002	1	6	2	60	Black (BK)	50
ShrinkKit 321 Universal	2	12	4	100	Black (BK)	15
	3	24	8	200	Black (BK)	10
	4	6	2	60	Green-Yellow (GNYE)	50
	5	3	1	50	Transparent (CL)	100
	6	3	1	50	Black (BK)	100
	7	12	4	100	Transparent (CL)	15
	8	12	4	100	Red (RD)	15
	9	3	1	50	Red (RD)	100
	10	3	1	40	Blue (BU)	100
	11	3	1	40	Green-Yellow (GNYE)	100
	12	1.5	0.5	40	Black (BK)	75
	12	1.5	0.5	40	Green-Yellow (GNYE)	75
	13	6	2	60	Blue (BU)	50
	14	6	2	60	Red (RD)	50
	15	6	2	60	Transparent (CL)	50
	16	12	4	170	Green-Yellow (GNYE)	10
	17	12	4	170	Blue (BU)	10

Pack Content

**New Standard:
Shrink Ratio 3:1**

ShrinKit 321-A

Features and Benefits

ShrinKit 321-A is dual wall heat shrink tubing with a 3:1 shrink ratio. The attractive and reusable kit is ideal for assembling and identification. The inner wall melts when heated and is forced into gaps. When the tubing cools down the adhesive forms a seal against the moisture and protects components. The black tubes are mainly used for the protection of connectors and splices, the clear tubing is ideal for the protection of printed label markers.

ShrinKit 321-A covers a wide range of applications due to its ideal 3:1 shrink ratio. When all tubing has been consumed the case can be re-used for storing nails, screws, nuts, fish hooks, et cetera. The size of the compartments can be changed by simply moving the yellow space dividers.

Content

This kit contains a range of general purpose tubing lengths clearly sorted. Four different sizes are included in black and clear.



ShrinKit 321-A: permanent protection of identification solutions.



ShrinKit 321-A.

Material Data

Material	Polyolefin, cross-linked (POX)
Shrink Ratio	3:1
Longitudinal change after shrinkage	+1%/-15% max.
Minimum Shrink Temperature	+110 °C
Operating Temperature	-55 °C to +110 °C
Insulation Class	A (VDE 0530)
Dielectric Strength	11,8 kV/mm according to ASTM D 2671
Flammability	self-extinguishing outer wall (black only)

New: With Adhesive

Technical Table

Article-No.	Comp.	Supplied Ø D min.	Recov. Ø d max.	Length (L)	Colour	Number of tubes
380-03003	1	24	8	200	Black (BK)	5
ShrinKit 321-A	2	12	4	65	Transparent (CL)	15
	3	6	2	50	Black (BK)	20
	3	6	2	50	Transparent (CL)	20
	4	12	4	65	Black (BK)	15
	5	3	1	50	Black (BK)	50
	5	3	1	50	Transparent (CL)	50
	6	6	2	35	Black (BK)	30
	6	6	2	35	Transparent (CL)	30
	7	24	8	200	Transparent (CL)	5
	8	12	4	100	Black (BK)	15
	9	12	4	100	Black (BK)	15
	10	12	4	100	Transparent (CL)	15
	11	3	1	40	Black (BK)	50
	11	3	1	40	Transparent (CL)	50

All Dimensions in mm. Subject to technical changes.

ShrinKit 321 Basic**Features and Benefits**

This compact and handy kit is part of the basic toolbox for every assembler. Its ideal shrink ratio of 3:1 replaces many differently sized tubings. An application range from 1 mm to 20 mm can be covered with ShrinKit 321 Basic.

Content

This kit contains a selection of widely used black tubing in five sizes and different lengths.



ShrinKit 321 Basic.

Material Data

Material	Polyolefin, cross-linked (POX)
Shrink Ratio	3:1
Longitudinal change after shrinkage	+5%/-10% max.
Minimum Shrink Temperature	+90 °C
Operating Temperature	-55 °C to +135 °C
Insulation Class	B (VDE 0530)
Dielectric Strength	20 kV/mm according to ASTM D 2671
Flammability	self-extinguishing

Technical Table

Article-No.	Comp.	Supplied Ø D min.	Recov. Ø d max.	Length (L)	Colour	Number of tubes
380-03001	1	1.5	0.5	35	Black (BK)	50
ShrinKit 321 Basic	2	6	2	35	Black (BK)	30
	3	3	1	35	Black (BK)	25
	4	6	2	35	Black (BK)	15
	5	6	2	35	Black (BK)	15
	6	3	1	35	Black (BK)	25
	7	1.5	0.5	35	Black (BK)	50
	8	18	6	80	Black (BK)	5
	8	12	4	80	Black (BK)	5

All Dimensions in mm. Subject to technical changes.

HellermannTyton

HellermannTyton
 Sharston Green Business Park
 1 Robeson Way
 Altrincham Road, Wythenshawe
 Manchester M22 4TY
 Tel: +44 161 945 4181
 Fax: +44 161 945 3708
 www.HellermannTyton.co.uk